

Electric Stretcher

Siderail-mounted power controls for backrest and knee gatch

Positioning controls easily accessible to patient and caregiver

Patient lock-out switches conveniently located at both ends of stretcher

Available with manual height adjustment or electric lift base



Effortless Patient Positioning

For longer-stay patients in the ER, PACU and observation units, Stryker offers a comfortable electric stretcher with power-assisted positioning controls. These powered adjustments also help increase staff efficiency and mitigate the risk of occupational injury by providing nearly effortless patient positioning.



Stryker's electric stretcher includes ergonomic enhancements for the benefit of patients and caregivers.

Accent Color Options



Electric Stretcher

stryker[®]



Medical

3800 E. Centre Ave.
Portage, MI 49002
t: 269 329 2100 f: 269 329 2311
toll free: 800 787 9537

www.stryker.com

Standard Features

- 4" (10 cm) Enhanced Comfort Mattress
- 30" (76 cm) wide patient surface
- 8" (20 cm) Omni Surface™ casters with wheel covers
- Dual-mounted collection device hooks
- Dual pedestal hydraulics
- Fold-down siderails
- Four IV receptacles
- Four-wheel, steel-ring brakes with dual end activators
- Hands-free Trend.
- Integrated storage tray with oxygen bottle holder
- Patient lock-out switches at head/foot ends
- Pop-up push handles
- Power litter (backrest and knee gatch) with manual crank backup
- Retractable fifth-wheel steering
- Rubber bumpers
- 8' (244 cm) breakaway coiled power cord
- Three-sided hydraulic controls
- Uni-lower pedal

Specifications

• Model Number	1550	
• Overall Length	83.5"	(212 cm)
• Overall Width	34"	(86 cm)
• Weight Capacity	500 lbs	(228 kg)
• Height Range		
High	35"	(89 cm)
Low	22"	(56 cm)
• Litter Positioning		
Electric Backrest	0° - 70°	
Manual Backrest	0° - 90°	
Knee Gatch	0° - 30°	
Trend./Reverse Trend.	±18°	
• Patient Surface	30" x 75.5"	(76 x 192 cm)
• Siderails	13" x 55"	(33 x 140 cm)
• Caster Diameter	8"	(20 cm)

Electronics

• Agency Approvals	US UL
• Volts	110 VAC
• Ampere Rating	7A
• Current Leakage	<100 microamperes
• Frequency	60 Hz
• Hospital Grade Plug	Yes

Stryker reserves the right to change specifications without notice.

Optional Features

- 4" (10 cm) or 5" (13 cm) Ultra Comfort Mattress
- Defibrillator tray
- Defibrillator tray/footboard/extender
- Dual lowering pedals
- Electric lift base
- Four-sided brake & steer pedals
- Footboard/chartholder
- Backrest X-ray cassette holder
- IV caddy
- IV poles
 - Permanent folding two- or three-stage
 - Tethered
 - Standard removable
- Patient restraints
- Quick-drop backrest
- Quick-drop backrest and knee gatch
- Serving/instrument tray
- Serving/instrument tray holder
- Siderail pads
- Upright oxygen bottle holder
- Extended warranty available
- Integrated Scale System

Copyright © 2005 Stryker
LSS-455-09D
PC/SCG-7.5M-0806
Mkt Lit-69-01262005 Rev D